

Vidar Series Thermal Imaging

Thermal Imaging scope Vidar335L

Technical Specifications

ThermTec Technology Co., Ltd. Email: info@thermeyetec.com Website: https://www.thermeyetec.com









VIDAR 335L

Key Features

- Compact design, video recording and snapshot, built-in memory chip up to 64GB
- 384*288 thermal resolution, NETD≤25mk
- Automatic object detection and laser ranging distance measurement up to 1,200m
- More accurate ballistic calculation
- Picture-in-picture & RAV function
- 1x--5x continuous digital zoom, 2 modes of Rapid and Smooth
- Various pesudo colors and crosshair function
- Polarity reversal for crosshairs, easy battery installation
- 1024*768 resolution with 0.39 inch OLED display
- Up to 14h continuous working for lithium battery

Applications

- Night hunting
- Observation
- Rescue operations
- Hiking and traveling

Specifications

	1			

			Function		
Model Vidar335L	Vidar335L	Max. recoil power			
		on rifled weapon	00003		
		Mounting	Chan doub Directions, Dail		
Туре	Uncooled	brackets on weapon	Standard Picatinny Rail		
Resolution	384x288	RAV	Yes		
Pixel pitch	12µm	Auto zeroing	Yes		
NETD	≤25mk	Manual zeroing	Yes		
Spectral range	8-14µm	Zeroing Profiles	5		
Frame rate	50HZ	Picture-in-picture	Yes		
Traine face	Optics	Laser rangefinder	1,200m		
	Optics	Ballistic calculator	Yes		
Objective lens	35mm, F1.0	Image calibration	Via lens cover		
			Video Recorder		
Field of view		Photo/video	Yes		
Field of view	7.5°x5.6°	playback Built-in memory	64GB		
			Interface		
Magnification	3.2X	Magnetic interface	Data Transfer		
Digital zoom	1.0-5.0X smooth & rapid zoom	Wi-Fi	Yes		
Eye relief	45mm		Battery		
Exit pupil	6mm	Replaceable	18650x2		
Diopter	±5D	battery Battery reverse			
5100000	Aiming Reticle	connection	Yes		
	Anning Reficie	Battery life	11h		
Click range, mm @100 m (H/V)	3.6m/3.6m		Environment		
		Operating temperature	-20°C—+50°C		
Reticle	7	IP rating	IP67		
Rectile color	Black and white	Weight, g	631		
	Display		031		
Туре	AMOLED	Dimension,mm	160(L) x 90(W) x 70(H)		
Resolution	1024x768				
Display size	0.39 inch	Magnetic cable	Accessories Magnetic interface data cable		
Color palette	6	Other accessory	Standard Picatinny Rail, eyeshade and etc.		





Dimension

Unit: mm

