



Thermal Imaging scope Vidar360 Technical Specifications

Download on the App Store







ThermTec Technology Co., Ltd. Email: info@thermeyetec.com Website: https://www.thermeyetec.com

VIDAR 360

Key Features

- Compact design, video recording and snapshot, built-in memory chip up to 64GB
- 384*288 thermal resolution, NETD≤25mk
- Automatic object detection and distance measurement
- Picture in picture & RAV function
- 1x--5x continuous digital zoom, 2 modes of Rapid and Smooth
- Various pesudo colors and crosshair function
- Polarity reversal for crosshairs, easy battery installation
- 1024*768 resolution with 0.39 inch OLED display
- Up to 14h continuous working for lithium battery
- Support easy shift of dual-field of view: focal length of 20/60mm

Applications

- Night hunting
- Observation
- Rescue operations
- Hiking and traveling

Specifications

Model	Vidar360
Mouel	Viuaisoo
Туре	Uncooled
Resolution	384x288
Pixel pitch	12µm
NETD	≤25mk
Spectral range	8-14µm
Frame rate	50HZ
	Optics
Objective lens	20/60mm F1.0
Field of view	13.1°x9.8°/ 4.4°x3.3°
Magnification	1.8X/5.5X
Digital zoom	1.0-5.0X smooth & rapid zoom
Eye relief	45mm
Exit pupil	6mm
Diopter	±5D
	Aiming Reticle
Click range, mm @100 m (H/V)	3.6m/3.6m
Reticle	7
Rectile color	Black and white
	Display
Туре	AMOLED
Resolution	1024x768
Display size	0.39 inch
Color palette	6

	Function
Max. recoil power	6000J
on rifled weapon	60000
Mounting brackets	Standard Picatinny Rail
on weapon RAV	-
	Yes Yes
Auto zeroing Manual zeroing	Yes
Zeroing profiles	5
Picture-in-picture	Yes
Image calibration	Via lens cover
	Video Recorder
Photo/video playback	Yes
Built-in memory	64GB
	Interface
Magnetic interface	Data transfer
Wi-Fi	Yes
	Battery
Replaceable battery	18650×2
Battery reverse connection	Yes
Battery life	14h
	Environment
Operating temperature	-20°C—+50°C
IP rating	IP67
Weight, g	880
Dimension, mm	220(L) × 84(L) × 87(L)
	Accessories
Magnetic cable	Magnetic interface data cable
Other accessories	Standard Picatinny Rail,eyeshade and etc.





Dimension

Unit: mm

